



PT. BESHA ANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240
Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600
E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id
Service : service@besha-analitika.co.id

List Kebutuhan Lab Prodi Farmasi UNIDHA Berdasarkan APTFI								
NO	ITEM	Spesifikasi	No. Cat	HARGA	Discoun	Best Price	Stock	Pembayaran
1	Compact HPLC with UV-Vis Detector  <i>Gambar Hanya Ilustrasi</i>	Compact HPLC with UV-Vis Detector Merk : Knauer GmbH - Germany Model : AZURA Specifications Key Features : Complete isocratic analytical HPLC system that needs very little bench space UV/VIS detector with one variable wavelength Pump unit with pressure sensor for a low pulsation eluent supply Optional AZURA Mobile Control software allows direct control of all integrated modules Leakage protection Complete software package ClarityChrom Complete sets consisting of : Azura Assistant ASM 2.2L : -Combine UV Vis Detector and Pump in One Housing -Left module: UV detector UVD 2.1S - ADA03XA -Middle module: Empty -Right module: Pump 4.1S 400 bar 10 mL Stainless Steel head -The Assistant ASM 2.2L is a docking station for three compact devices -The plug-in modules are removed by loosening four screws allowing the user to exchange modules in case of service within minutes. Likewise, the configuration of the LC system can be adapted to new requirements Routine maintenance work e.g. replacing the lamp of a detector is easily performed by the user. UV Detection Module : -Compact variable single wavelength UV - Vis Detector -Wavelength ranges : 190 - 500 nm -Spectral bandwidth : 13 nm -Light source : Deuterium (D2) Lamp with integrated GLP Chips -Wavelength accuracy +/- 3 nm	Azura	Rp517.948.200	5%	Rp492.050.790	1 unit	50% DP, 50% sebelum barang dikirim
2	Isocratic HPLC with UV-Vis Detector  <i>Gambar Hanya Ilustrasi</i>	Isocratic HPLC with UV-Vis Detector Merk : Knauer GmbH - Jerman Model : Azura 862 Complete Sets Consisting of : -1 pcs AZURA® Pump P 6.1L isocratic, without degasser, with 10 ml pump head (stainless steel) -1 pcs Eluent Tray AZC 00 -1 pcs Eluent bottles 1000 ml -1 pcs AZURA Tubing Kit (1/8", FEP) with cap and inset, solvent filter inlet and fittings -1 pcs Manual Injection Valves 500 Bar -1 pcs Sample loops 20 uL -1 pcs Ler Lock Syringes + Luer Adapter -1 pcs Mounting Bracket -1 pcs ClarityChrom 9.1.0 station single instrument license one time base -1 pcs AZURA® UVD 2.1L UV Vis Detector (190-750 nm) -1 pcs Flow Cell for UVD 2.1L Detector -1 set Start-up & installations Tubing Kit for analytical HPLC -1 set Tools kit -1 pcs HPLC C18 / ODS Column 150 x 4.6 mm -1 set PC Computer and Printer -1 pcs Switch / Hub 8 Port	Azura	Rp543.300.016	5%	Rp516.135.015	Indent 3-4 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHA ANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240

Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600

E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id

Service : service@besha-analitika.co.id

3	Quaternary Gradient HPLC with UV-Vis Detector  Gambar Hanya Ilustrasi	Quaternary Gradient HPLC with UV-Vis Detector Merk : Knauer GmbH - Jerman Model : Azura 862 Complete Sets Consisting of : -1 pcs AZURA Gradient Pump P 6.1L Pump P 6.1L (LPG) with 10 ml pump head 862 bar max pressure, 4 channel online degasser, and gradient mixers 600 uL -1 pcs Eluent Tray AZC 00 -1 Set of 4 eluent bottles 1000 ml, 1 bottle 250 ml for piston backflushing, incl. closed caps, GL45 use with AZURA tubing kit -1 pcs AZURA Tubing Kit (1/8", FEP) with cap and inset, solvent filter inlet and fittings -1 pcs Manual Injection Valves 500 Bar -1 pcs Sample loops 20 uL -1 pcs Ler Lock Syringes + Luer Adapter -1 pcs Mounting Bracket -1 pcs ClarityChrom 9.1.0 station single instrument license one time base -1 pcs AZURA® UVD 2.1L UV Vis Detector (190-750 nm) -1 pcs Flow Cell for UVD 2.1L Detector -1 set Start-up & Installations Tubing Kit for analytical HPLC -1 set Tools kit -1 pcs HPLC C18 / ODS Column 150 x 4.6 mm -1 set PC Computer and Printer -1 pcs Switch / Hub 8 Port	Azura	Rp679.493.578	5%	Rp645.518.899	Indent 3-4 bulan	50% DP, 50% sebelum barang dikirim
4	Binary High Pressure Gradient HPLC with UV-Vis Detector  Gambar Hanya Ilustrasi	Binary High Pressure Gradient HPLC with UV-Vis Detector Merk : Knauer GmbH - Jerman Model : Azura 862 Complete Sets Consisting of : -1 pcs AZURA Gradient Pump P 6.1L Pump P 6.1L (HPG) with 10 ml pump head 862 bar max pressure, 2 channel online degasser, and gradient mixers 400 uL -1 pcs Eluent Tray AZC 00 -1 Set of 2 eluent bottles 1000 ml, 1 bottle 250 ml for piston backflushing, incl. closed caps, GL45 use with AZURA tubing kit -1 pcs AZURA Tubing Kit (1/8", FEP) with cap and inset, solvent filter inlet and fittings -1 pcs Manual Injection Valves 500 Bar -1 pcs Sample loops 20 uL -1 pcs Ler Lock Syringes + Luer Adapter -1 pcs Mounting Bracket -1 pcs ClarityChrom 9.1.0 station single instrument license one time base -1 pcs AZURA® UVD 2.1L UV Vis Detector (190-750 nm) -1 pcs Flow Cell for UVD 2.1L Detector -1 set Start-up & Installations Tubing Kit for analytical HPLC -1 set Tools kit -1 pcs HPLC C18 / ODS Column 150 x 4.6 mm -1 set PC Computer and Printer -1 pcs Switch / Hub 8 Port	Azura	Rp720.020.737	5%	Rp684.019.700	Indent 3-4 bulan	50% DP, 50% sebelum barang dikirim
5	Turbidimeter  Gambar Hanya Ilustrasi	Turbidimeter Merk : Eutech Model : TN100 Spesification : Measuring Parameter : Turbidity Highlights : Light weight, IP67 waterproof meter Principle : Nephelometric non-ratio / ISO 7027 and DIN 27027 compliant Range : 0 to 2000 NTU Automatic Range Selection : 0.01 to 19.99 NTU; 20.0 to 99.9 NTU; 100 to 2000 NTU Resolution : 0.01 NTU (0 to 19.99 NTU); 0.1 NTU (20.0 to 99.9 NTU); 1 NTU (100 to 2000 NTU) Accuracy : < 0.1 NTU for 0.02 NTU standard; ±2 % of reading ±1 digit for 0 to 500 NTU; ±3 % of reading ±1 digit for 501 to 2000 NTU Repeatability : < or = ±1 % of reading Calibration : Up to 4 points Calibration Standards : 0.02 NTU, 20.0 NTU, 100 NTU, 800 NTU Response Time : < 6 secs for full step change Sample Volume : 10 mL Light Source : Infrared-emitting diode (850 nm wavelength) Operating Temperature Range : 0 to 50 oC Sample Temperature Range : 0 to 50 oC Enclosure Type & Rating : ABS plastic & IP67 rated Power : 4 x 1.5 V 'AAA' alkaline batteries (> 1200 readings) Dimensions (LxWxH) :	TN100	Rp37.860.250	5%	Rp35.967.238	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHA ANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240
Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600
E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id
Service : service@besha-analitika.co.id

6	Moisture Balance resolusi 0.01 % moisture, 1 mg timbang, kapasitas timbang 160 gram  Gambar Hanya Ilustrasi	Moisture Balance resolusi 0.01 % moisture, 1 mg timbang, kapasitas timbang 160 gram Merk : Bel Engineering - Italy Model : I Thermo G163L Specification : High readability load cell weighing system Halogen-infrared lamp Large Graphic display allows efficient and easy operations Date and time indication Two heating modes: standard and rapid Pre-heating on/off Time (1-99 min) and Autostop operating model Temperature range: 35-160°C/1°C Moisture, dry residue in percentage and AT RO indications RS232 serial interface Max : 160 g Readability : 0.001 gr Moisture readability : 0.01% Moisture Repeatability : ± 0.20% (~2g sample) Pan : 100mm Samples Pan Drying temperature range : 35~160°C Response time (sec.) : ≤ 4 Dimensions LxWxH (mm): 345x215x235 Maximum dimension of container on the pan: 100mm (Ø) x 25mm (height) Power supply 110-230Vac,output 9V 1,2A 10VA [other models] Heater: 230V AC 50/60Hz, 400Watt Setiap Moisture balance sudah termasuk : -1 set Unit utama -1 pak Re-usable Drying Pan 80 mm dia , pk/80 pcs	I Thermo G163L	Rp47.368.421	5%	Rp45.000.000	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
7	Digital Colony Counter  Gambar Hanya Ilustrasi	Digital Colony Counter Merk : Synbiosis Co Ltd - UK Model : Accolade 2 Specifications : -The colony counter consists of an illuminated receiver plate and a large LED display. -The pressure of marking a colony with a felt-tip pen registers a cumulative count on the digital display with confirmation by audible tone (can be turned on or off). -The pressure required to register a count can be adjusted to suit each user -Sub-stage illumination by low energy bright LEDs allows glare-free optimum viewing. -A switchable black background is provided to enhance viewing of translucent and difficult to see colonies. -Lighting : White LED array -Display : digital 3 Digit LCD -Counting ranges : 0 - 999 counts -Dimensions : 310 x 300 x 140mm -Nett Weight : 1.5 Kg -Voltage Ranges : 90 - 240 Volts 50/60 Hz Complete with : -2 pcs graticules and Dish Centering adapters for 50 mm – 90 mm dishes (terpasang) -1 pcs Magnifier 1.7x magnifications (terpasang) -1 sets SOP Bahasa Indonesia -1 pcs Video Pemakaian Alat Bahasa Indonesia	Accolade 2	Rp48.190.211	5%	Rp45.780.700	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
8	Automatic Digital Melting Point Apparatus  Gambar Hanya Ilustrasi	Automatic Digital Melting Point Apparatus, Merk : Biobase Model : BMP-2C Spesification : -PID&PWM controller. -Touch screen. -Equipped with clock function. -The melting curve can be recorded automatically. -It can calculate average value of initial and final melting points automatically. -Can connect to a computer for data transferring. -Measuring Range : RT~360°C -Resolution : 0.1°C -Linear Heating-up Rate : 0.1°C/min~20°C/min -Temperature Accuracy : ±0.4°C(≤200°C), ±0.7°C(>200°C) -Repeatability : 0.3°C(Heating rate: 1.0°C/min) -Capillary Size : φ1.4mm(outside diameter), φ1.0mm(inside diameter), 90mm(length) -Sample Loading Height : 3mm -Data Storage : 1000 sets -Interface : RS232, USB -Power Supply : AC110~240V, 50/60Hz	BMP-2C	Rp94.736.842	5%	Rp90.000.000	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHA ANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240

Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600

E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id

Service : service@besha-analitika.co.id

9	Digital Automatic Polarimeter	 Gambar Hanya Ilustrasi	Digital Automatic Polarimeter Merk : Biobase - China Model : BK-P2S Spesification : Light Source : LED+interference filter Measuring Range : $\pm 45^\circ$ (optical rotation) $\pm 120^\circ$ Z(sugar) Wavelength : 589nm Readable Accuracy : 0.001° (optical rotation) 0.01° Z(sugar) Measuring Accuracy : $\pm (0.01 + \text{measurement value} \times 0.05\%)$ (optical rotation) $\pm (0.03 + \text{measurement value} \times 0.05\%)$ Z(sugar) Repeatability : $\leq 0.002^\circ$ (optical rotation) Test Mode : Optical rotation, sugar degree Test Tube : 200mm, 100mm Sample Transmittance : 1% Interface : RS232 Power Supply : AC110/220V, 50/60Hz External Size(W/D/H) : 570*350*280mm	BK-P2S	Rp97.212.500	5%	Rp92.351.875	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
10	Benchtop Centrifuge dengan rotor 6 x 50 mL	 Gambar Hanya Ilustrasi	Benchtop Centrifuge dengan rotor 6 x 50 mL Merk : Biomed Lab - China Model : BG16000 Spesification : Model : BG16000 (touch screen) Max. RPM/RCF for angle rotor : 16000rpm / 21627×g Max. RPM/RCF for swing rotor : 4000rpm / 4924×g Max. Capacity for angle rotor : 4×100ml, 48×1.5/2.2ml Max. Capacity for swing rotor : 4×400ml, 96-well plates Speed Accuracy : ± 20rpm Timer Range : 0min-99min59s / continuous Acc / Dec rates : 16/16 Program Memory : 100 Short spin function Power Supply : AC220V / 50-60Hz Power Requirement : 750W Noise : <55db Screen : LCD touch screen Machine Body : Plastic and metal frame Net Weight (without rotor) : 38kg Machine Dimension(L×W×H): 460×570×360mm Kelengkapan : Sudah termasuk 1 bh unit utama dengan layar touchscreen, 1 bh rotor 6x50 mL, 1 bh buku petunjuk pemakaian dan 1 bh kabel listrik, 1 set Tabung Sentrifus 50 mL, kemasan 50 pcs	BG16000	Rp82.400.842	5%	Rp78.280.800	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
11	Digital Automatic Rotary Evaporator with Vertical Condenser and Motorized Lift	 Gambar Hanya Ilustrasi	Digital Automatic Rotary Evaporator with Vertical Condenser and Motorized Lift Merk : Boco GmbH - Germany Model : RVO-400SD Order No : BOE 8090020 Specifications : -Conforms to the CE mark and all relevant EC standards and DIN norms and has been manufactured under ISO 9001:2000 -Rotary Evaporator systems with a motorized lift and built-in vacuum controller -Cooler Condensations size : (1200 cm 2) or larger -Controller : With digital display and control -Variable / adjustable inclination angle of evaporating flask -It has a function of pressure and temperature gradient -Possible receiving flasks: 100 - 2000 ml -Possible Evaporating flasks: 20 - 4000 ml -Rotation speed of the evaporating flask : programmable 0 - 280 rpm -Bath temperature: max. 100°C for water filling max. 180°C for oil filling -Bath Temp. accuracy: $\pm 1^\circ\text{C}$ up to 100°C $\pm 3^\circ\text{C}$ up to 180°C -Vacuum Pressure measurement: absolute -Pressure difference is adjustable adjustable : 1-500 mbar. -Digital display and settings for : Temperature, rotations, vacuum -Digital Gradient settings for Temperature, pressure -Adjustable unit of measurement : temperature unit selection: °C, °K Pressure units selections: hPa, Torr -Switched vacuum pump: output max 650 VA, input max. 2000 VA -Power supply: 230 V $\pm 10\%$, 50/60 Hz -Power input: max. 2000 W (excluding vacuum pump) -Dimensions in mm (W×H×D): 650 x 900 x 360 (incl. glass) -Net weight: approx 20 kg Includes : -1 sets of glassware with Vertical Condenser with 1200 cm2 condensation size	RVO-400SD	Rp163.400.526	5%	Rp155.230.500	Indent 2 1/2-3 1/2 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240

Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600

E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id

Service : service@besha-analitika.co.id

12	UV-Vis Spectrophotometer	 Gambar Hanya Ilustrasi	UV-Vis Spectrophotometer Merk : MicroDigital - Korea Model : UBI-600 Specification : Photometric Range : 0-200%T, -3.0-3.0A, 0-9999C Spectral Bandwidth : 1.8nm Wavelength Range : 190 - 1,100nm Wavelength Accuracy : ± 0.5 nm Wavelength Repeatability : ± 0.2 nm Stray Light : $\leq 0.05\%T_{220nm}$, 360nm Photometric Accuracy : $\pm 0.2T(0-100\%T) / \pm 0.002Abs(0-0.5Abs) / \pm 0.004Abs(0.5-1.0Abs)$ Photometric Repeatability : $\pm 0.05\%T(0-100\%T) / 0.001Abs(0-0.5Abs) / 0.002Abs(0.5-1.0Abs)$ Stability : $\pm 0.001A/h@500nm$ Baseline Flatness : $\pm 0.001A$ Noise : $\pm 0.005A$ Display : 7-inch (800 x 480px) Touch Screen Data Output & Print Port : USB Light Source : Tungsten Halogen Lamp & Deuterium Lamp Power Requirements : AC220V/50Hz Detector : Silicon Photodiode Dimension : 460 x 380 x 180mm Complete with : -1 sets PC Computer & Printer -1 pcs 8 Cell Holder	UBI-600	Rp159.353.158	5%	Rp151.385.500	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
13	Friability Tester	 Gambar Hanya Ilustrasi	Friability Tester Merk : Biobase - China Model : TFT-1 Specification : - Automation : auto-test, auto-diagnose, auto alarm - Cylinder Number : 2 - Cylinder Radius : $\phi 286$ - Cylinder dept : 39 mm - Tablet Fall Height : 156 mm - Rotating speed : 20-100 rpm - Rotating Count : 5-900 turns - Consumption : 40W - Power Supply : AC110/220V $\pm 10\%$, 50/60HZ - External Size(W*D*H)mm : 370 x 300 x 340	TFT-1	Rp85.294.737	5%	Rp81.030.000	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
14	Tapped Density Tester	 Gambar Hanya Ilustrasi	Tapped Density Tester Merk : Biobase - China Model : BKDT-100B Specification : Powder Density Tester with micro printer Benchtop Tap Density Volumeter Sample : 500g Sample volume: 250ml Single vibration number: 99999 Motor torque: 0.86 N.m Frequency: max 300rpm continuous adjustable in 0-300rpm Amplitude: max 15mm Repeatability: 1% Accuracy: 1% Power supply: AC 220V/50Hz, Power: 40W	BKDT-100B	Rp69.405.474	5%	Rp65.935.200	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
15	Tablet Hardness Tester	 Gambar Hanya Ilustrasi	Tablet Hardness Tester Merk : Biobase - China Model : THT-2 Specification : - LCD Display, High-precision pressure sensor ensures the precision andreproducibility of test. - Automatic display, automatic latching, automatic reset, automatic cycle test, automatic linear error correction and automatic fault diagnosis. - Test Range : 2-200N/500N(0.2-20kg) - Resolution : 0.1N 0.01kg - Accuracy : $\pm 0.5\%$ - Probe Procession Range : 2-40mm - Consumption : 40W - Power Supply : AC110/220V $\pm 10\%$, 50/60HZ - Dimensions(W*D*H)mm : 500x400x160	THT-2	Rp58.847.895	5%	Rp55.905.500	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240

Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600

E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id

Service : service@besha-analitika.co.id

16	Ultrasonic Homogenizer  Gambar Hanya Ilustrasi	Ultrasonic Homogenizer Merk : Bandelin GmbH - Germany Model : HD 4100 Specifications : -Typical area of applications : disruptions of cells, bacteria, viruses, tissue or mixed of tissue Emulsifying of hard yto mixed liquids such as oil and water, and particle size in micrometer ranges Deagglomeration of nano particles in material research in medicine, biotechnology and medicine -Amplitude control : 10 - 100 % -Power control : HF Power -Automatic amplitude limiting : Yes -Display : alphanumeric LCD showing of amplitude, pulsation, time , mode and energy -Pulsation : ON Cycle 0.2 Seconds to 600 seconds, OFF Cyle 0.3 seconds up to 600 seconds -Timer : up to 9 hours, 59 minutes, 59 seconds -Energy monitoring : in Kjoule -Number of prorgam : up to 9 programs -Processing Frequency : 20 KHz -Remote control with PC Computer : RS-232 -Voltage : 220 Volts 50 Hz Includings : 1x Ultrasound generator GM 4200, 1x Ultrasonic converter UW 100, 1x Standard horn SH 100 G, 1x probe TS 103	HD4100	Rp136.160.526	5%	Rp129.352.500	Indent 2 1/2-3 1/2 bulan	50% DP, 50% sebelum barang dikirim
17	Climate chamber, 256 Liter  Gambar Hanya Ilustrasi	Climate chamber, 256 Liter Merk : Memmert GmbH - Germany Model : ICH260 Spesification : Temperature Setting temperature range : -10 to +60 °C Working temperature range : from -10°C up to +60°C without humidity(not suitable for long-term storing at sub-zero temperatures. During permanent operation, the glass door may ice over) Working temperature range : from +10°C up to +60°C with humidity and/or light Setting accuracy temperature : 0.1 °C Temperature sensor : 2 Pt100 sensors DIN Class A in 4-wire-circuit for mutual monitoring, taking over functions in case of an error Humidity Humidity : humidity supply with distilled water from external tank by self-priming pump Humidification : humidification by hot steam generator Humidity : active humidifying and de-humidifying adjustable from 10-80 % rh with digital display of relative humidity - resolution of display 0.1 % , setting accuracy 0.5 % Control technology ControlCOCKPIT : TwinDISPLAY. Adaptive multifunctional digital PID-microprocessor controller with 2 high-definition TFT-colour displays. adjustable parameters : temperature (Celsius or Fahrenheit), fan speed, relative humidity, programme time, time zones, summertime/wintertime Timer : Digital backwards counter with target time setting, adjustable from 1 minute to 99 days Function SetpointWAIT : the process time does not start until the set temperature is reached Heating concept Air jacket : air jacket heating system for gentle all-around heating	ICH260	Rp386.404.000	5%	Rp367.083.800	Indent 4-5 bulan	50% DP, 50% sebelum barang dikirim



PT. BESHANALITIKA

Jl. Boulevard Barat Komplek Gading Bukit Indah Blok N No. 23
Kelapa Gading Barat, Kelapa Gading, Jakarta Utara, DKI Jakarta Raya 14240
Telp. : (021) 4585 6666 (Hunting) Fax. : (021) 4585 7600
E-mail : info@besha-analitika.co.id, Website : www.besha-analitika.co.id
Service : service@besha-analitika.co.id

18	Digital Handheld Rotary Viscometer	 Gambar Hanya Ilustrasi	Digital Handheld Rotary Viscometer Merk : ProRheo GmbH - Germany Model : R120 Specifications : -Rotational viscometer for viscosity measuring according ISO and DIN. -Easy handling and a Large measuring range. -Three selectable Rotational speeds. -One measuring system only, avoiding errors because of measuring system selection. -viscosity display in Pas or mPas -measuring principle Rotational viscometer -Rotational speed : 20 – 1000 min-1 -Torque ranges : up to 10 mNm -Viscosity ranges : 20 mPas – 10 6 Pas -display : digital LCD -Voltage : 230 Volts 50 Hz Complete with : -1 pcs AC Adapter for 230 Volts 50 Hz -1 pcs Carrying Case -1 sets Measuring Systems -1 pcs Tripod	R120	Rp132.787.547	5%	Rp126.148.170	Indent 2 1/2-3 1/2 bulan	50% DP, 50% sebelum barang dikirim
19	Benchtop PH/mV Meter	 Gambar Hanya Ilustrasi	Benchtop PH/mV Meter Merk : Eutech Model : PH 1710 Specification : -Simultaneously read pH, mV and temperature -Measure -2.00 to 18.00 pH, ± 2000.0 mV, -5.0 to 105.0°C -Perform one- to five-point pH calibrations -Calibrate using automatic buffer recognition or manual entry -Perform one-point relative mV calibration (RmV) -Monitor pH electrode status with the electrode condition icon -View pH, RmV and temperature calibration logs with date and time stamps -All data and calibration logs are date and time stamped for GLP/GMP reporting -Help facilitate electrode movement into and out of samples with the meter-attached stand -pH : range : -2.00 to 18.00 pH resolution : 0.1, 0.01 pH relative accuracy : ± 0.01 pH ± 1 LSD Calibration points : 1 to 5 points Include : Buffer Solution	PH1710	Rp25.170.000	5%	Rp23.911.500	Indent 2-3 bulan	50% DP, 50% sebelum barang dikirim
20	Universal Oven, 53 Liter	 Gambar Hanya Ilustrasi	Universal Oven, 53 Liter Merk : Memmert GmbH - Germany Model : UN55 Specification : Convection : natural convection Fresh air : Admixture of pre-heated fresh air by electronically adjustable air flap Vent : vent connection with restrictor flap Volume: 53 l Dimensions : w(A) x h(B) x d(C): 400 x 400 x 330 mm Max. number of internals : 4 Max. loading of chamber : 80 kg Max. loading per internal : 20 kg Working temperature range : above ambient temperature to +300 °C Setting accuracy temperature : up to 99.9 °C: 0.1 / from 100 °C: 0.5 Setting temperature range : +20 to +300°C Ambient temperature : +5 °C to +40 °C Humidity rh : max. 80 %, non-condensing Max. loading of chamber : 300 kg Max. loading per internal : 20 kg	UN55	Rp44.585.263	5%	Rp42.356.000	Indent 4-5 bulan	50% DP, 50% sebelum barang dikirim
Total							Rp3.923.443.687		50% DP, 50% sebelum barang dikirim
NB :									
Harg termasuk PPN 11% Garansi 1 tahun Free instalasi dan training Estimasi Pengiriman sesuai dengan Informasi Ketersediaan di Stok									